



Fill-Putty™



Description:

Fill-Putty™ is an anticorrosive moldable filler material used to even the contours of irregular fittings and surfaces. Once applied, it is overwrapped with Trenton's Wax-Tapes®.

Application:

Brush or wipe the surfaces clean of dirt, loose rust or old coating and other foreign materials. Apply Fill-Putty directly by hand, working the material onto the metal surface ensuring that the putty is "wetting" and adhering to the surface.

Continue applying the material in and around the voids, contours and crevices so as to build up an even surface all around the fitting or structure.

Then overwrap the entire application with Trenton's Wax-Tapes.

Packaging:

2 inch diameter by 13 inch long links
20 links per case
40 lbs. per case

Specifications:

Specific Gravity	1.15
Density	24 cu. in. per lb.
Application Temperature	40°F to 140°F
Service Temperature.....	140°F Maximum
Flash Point.....	350°F Minimum
Pour Point	240°F



Corporate Office:

7700 Jackson Road
Ann Arbor, MI 48103 USA
(734) 424-3600
Fax: (734) 426-5882
trenton@trentoncorp.com

Houston Office:

1880 S. Dairy Ashford Rd.
Suite #697
Houston, Texas 77077 USA
(281) 556-1000
Fax: (281) 556-1122
tweber@trentoncorp.com

European Office:

15, rue Beaujon
Paris 75008
France
+33 (0) 1 42 99 95 78
Fax: +33 (0) 1 77 65 62 99
europe@trentoncorp.com

www.trentoncorp.com