



Pre-Con®



Pre-Con® being poured into the casing through the casing vent.

Description:

Pre-Con® is a liquid casing water conditioner for pipeline casings. It consists of "wetting" and filming agents, vapor phase inhibitors, alkaline media additives and antibacterial conditioners.

End Use:

Pre-Con is poured into the casing prior to the installation of Trenton Fill-Coat® Casing Filler. The method of using these two materials together is a Trenton Corporation patented process.*

Pre-Con conditions the water accumulated in the casing so that any small amounts of water that may be entrapped after installation of Fill-Coat Casing Filler are inhibited and no corrosion should occur.

Application Procedures:

Prior to the filling operation, Pre-Con is poured directly into the casing through the casing vent and mixes with any water accumulated inside the casing. The casing can then be filled with Trenton Fill-Coat Casing Filler.

Packaging:

Pre-Con is packaged in five-gallon pails or is provided in bulk at the job site when Trenton crews install Fill-Coat Casing Filler.

Specifications:

Solubility in water	100%
Specific gravity	1.13
Color	Amber
Flash point	None

Advantages:

Five gallons per 1,000 gallons of casing capacity.



Corporate Office:

7700 Jackson Road
Ann Arbor, MI 48103 USA
(734) 424-3600
Fax: (734) 426-5882
trenton@trentoncorp.com

Houston Office:

1880 S. Dairy Ashford Rd.
Suite #697
Houston, Texas 77077 USA
(281) 556-1000
Fax: (281) 556-1122
tweber@trentoncorp.com

European Office:

15, rue Beaujon
Paris 75008
France
+33 (0) 1 42 99 95 78
Fax: +33 (0) 1 77 65 62 99
europe@trentoncorp.com

www.trentoncorp.com